




TORO-IRRIGATION DIVISION  
 5825 JASMINE STREET  
 RIVERSIDE, CA 92504  
 TOLL FREE: 1-877-345-8676  
 FAX: (951) 359-1870  
 crc@toro.com  
 www.toro.com



ELEVATION/SECTION  
 NOT TO SCALE


MIN. FLOW RATE - 0.25GPM  
 MAX. FLOW RATE - 8.0 GPM

LEGEND:

- ① CONTROL WIRES WITH 12" SERVICE COIL AND WATER PROOF WIRE CONNECTIONS, DBY OR EQUAL.
- ② TORO EZF-29-03 ANTI-SIPHON VALVE (\*).
- ③ TORO 150 MESH Y-FILTER (\*).
- ④ TORO 25 PSI LOW FLOW PRESSURE REGULATOR (\*).
- ⑤ SCH 80 PVC CLOSE NIPPLE (\*).
- ⑥ SCH 40 PVC BALL VALVE (\*).
- ⑦ SCH 40 PVC MALE ADAPTER.
- ⑧ CONTROL WIRES TO CONTROLLER.
- ⑨ PVC MAINLINE PER SPECIFICATIONS.
- ⑩ PVC MAINLINE FITTING.
- ⑪ NATIVE SOIL PER SPECIFICATIONS.
- ⑫ PVC LATERAL LINE PER SPECIFICATIONS.
- ⑬ FINISH GRADE.
- ⑭ PVC SCH 40 ELL (SxS).
- ⑮ LATERAL LINE TO DRIP SYSTEM.
- ⑯ HEIGHT ABOVE GRADE PER LOCAL CODES (6" MINIMUM).  
 (\*) PARTS IN DRIP ZONE KIT.

NOTES:

1. LOCATE STAPLES ALONG TUBING AT 4'-6" ON CENTER AND AT ALL FITTINGS (TEES, ELLS, ETC.)
2. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
3. DO NOT SCALE DRAWING.
4. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
5. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
6. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT [www.CADdetails.com/info](http://www.CADdetails.com/info) AND ENTER REFERENCE NUMBER 065-190e.



**TORO DRIP ZONE KIT**

DZK-2711-075-LF