




TORO-IRRIGATION DIVISION
 5825 JASMINE STREET
 RIVERSIDE, CA 92504
 TOLL FREE: 1-877-345-8676
 FAX: (951) 359-1870
 crc@toro.com
 www.toro.com



ELEVATION/SECTION
 NOT TO SCALE


MIN. FLOW RATE - 0.20 GPM
 MAX. FLOW RATE - 20.0 GPM

LEGEND:

- ① CONTROL WIRES WITH 12" SERVICE COIL AND WATER PROOF WIRE CONNECTIONS, DBY OR EQUAL.
- ② TORO EZF-29-03 ANTI-SIPHON VALVE (*).
- ③ TORO 150 MESH Y-FILTER (*).
- ④ TORO 25 PSI LOW FLOW PRESSURE REGULATOR (*).
- ⑤ SCH 80 PVC CLOSE NIPPLE (*).
- ⑥ SCH 40 PVC BALL VALVE (*).
- ⑦ SCH 40 PVC MALE ADAPTER.
- ⑧ CONTROL WIRES TO CONTROLLER.
- ⑨ PVC MAINLINE PER SPECIFICATIONS.
- ⑩ PVC MAINLINE FITTING.
- ⑪ NATIVE SOIL PER SPECIFICATIONS.
- ⑫ PVC LATERAL LINE PER SPECIFICATIONS.
- ⑬ FINISH GRADE.
- ⑭ PVC SCH 40 ELL (SxS).
- ⑮ LATERAL LINE TO DRIP SYSTEM.
- ⑯ HEIGHT ABOVE GRADE PER LOCAL CODES (6" MINIMUM).
- (*) PARTS IN DRIP ZONE KIT.

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 065-190b.



TORO DRIP ZONE KIT

DZK-EZF-075-MF