



- ① TORO T-P2S (2-1/2" INLET) OR T-P2M (3" INLET) SERIES SPRINKLER.
- ② QUICK CONNECT - ALUMINUM TYPE B x MIPT (SIZED TO PIPE).
- ③ QUICK CONNECT - ALUMINUM TYPE F x MIPT (SIZED TO PIPE).
- ④ BRASS BALL VALVE W/PADLOCK SAFETY FEATURE - FULL PORT - FIPT INLET/OUTLET (SIZED TO PIPE).
- ⑤ TORO STAINLESS STEEL VALVE BOX - TSSBKC-18-SOLID W/RECESSED STAINLESS STEEL LID AND 1/2-INCH THICK HDPE INSERT FROM THE UNDERSIDE - 18"W x 18"L x 18"D - VALVE BOX HAS INTERNAL STAINLESS STEEL STABILIZER TO CENTER AND MAINTAIN VERTICALITY.
- ⑥ HDPE OR WOOD SIDE SUPPORTS - ADJUST FOR VARYING PILE HEIGHTS. SECURE TO ALL FOUR SIDES OF EACH VALVE BOX.
- ⑦ INTERNAL PIPING STABILIZER SUPPLIED WITH TORO VALVE BOX TSSBKC-18-SOLID.
- ⑧ IRRIGATION WATER LINE PIPING SUPPLIED BY OTHERS.
- ⑨ 3/4" WASHED GRAVEL BACKFILL - SET TO 6" BELOW BOX.
- ⑩ COMMON RED OR CONCRETE BRICK SUPPORT UNDER EACH CORNER OF BOX. TYPICAL.
- ⑪ COMPACTED SUB-BASE MATERIAL.
- ⑫ FINISH GRADE.

TORO P2 SERIES SPRINKLER

GROUND INSTALL WITH QUICK DISCONNECT