




TORO-IRRIGATION DIVISION
 5825 JASMINE STREET
 RIVERSIDE, CA 92504
 TOLL FREE: 1-877-345-8676
 FAX: (951) 359-1870
 crc@toro.com
 www.toro.com

<u>SYMBOL</u>	<u>MODEL NO.</u>	<u>DESCRIPTION</u>
	TMC-424E-xx	TORO TMC-424E SERIES (CONSIDER USING CUSTOM COMMAND OR TDC WHEN CONTROLLING MULTIPLE FIELDS) INCLUDE TMR-1 KIT FOR HAND-HELD REMOTE CONTROL CAPABILITY
	TWRS/TWRFS	TORO WIRELESS RAIN (RAIN/FREEZE) SWITCH
		ESTIMATED STATION COUNT
		GATE VALVE LINE SIZED INSTALL IN 10" ROUND VALVE BOX WITH COVER
	P220-26-06	TORO P220 SERIES ELECTRIC VALVE INSTALL IN 10" ROUND VALVE BOX WITH COVER
	220-26-08	TORO 220 SERIES BRASS MASTER VALVE (USE 220-27-08 IF OVER 125 PSI AT POC) INSTALL IN 10" ROUND VALVE BOX WITH COVER
	T7P #16 NOZZLE	TORO T7P SERIES SPRINKLER (50-55' SPACING, 59' RADIUS, 16.2 GPM @ 60.0 PSI)
	100-SLSC	TORO 1" ONE-PIECE QUICK COUPLER VALVE WITH STANDARD COVER AND WITH #100-SLK KEY INSTALL QCV IN 6" VALVE BOX WITH COVER
		MAINLINE PVC PIPE (2-1/2" UNLESS OTHERWISE NOTED)
		LATERAL PVC PIPE (2" UNLESS OTHERWISE NOTED)
		REDUCED PRESSURE ASSEMBLY BACKFLOW PREVENTER
		POINT OF CONNECTION
		WATER SOURCE

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 065-456a.



OFFICIAL H.S. SOCCER FIELD: FOUR-ROW, END FEED

LEGEND