


SECTION/ELEVATION
NOT TO SCALE

LEGEND:

- ① 1" ABOVE FINISH GRADE.
- ② FINISH GRADE.
- ③ TORO FLUSH VALVE (T-FCH-H-FHT).
- ④ TORO TRI-LOC X 3/4" MPT ADAPTER (TL-M75) OR I560-M75 INSERT X 3/4" MPT ADAPTER.
- ⑤ TORO BLUE STRIPE POLY TUBING (T-EHX1554-XXX).
- ⑥ TORO DRIP IN® 17MM DRIPLINE TUBING (PCB-XXX-XXX) OR TORO BLUE STRIPE POLY TUBING (T-EHX1554-XXX).
- ⑦ 6" ROUND PLASTIC VALVE BOX . HEAT BRAND "FV" ON LID IN 1" HIGH CHARACTERS.
- ⑧ TORO TRI-LOC ELBOW (TL-E) OR I560-E INSERT ELBOW.
- ⑨ BRICK SUPPORTS (2 COMMON BRICKS REQUIRED).
- ⑩ NATIVE SOIL PER SPECIFICATIONS.
- ⑪ PEA GRAVEL SUMP (6" x 18").

NOTES:

1. USE ONE FLUSH VALVE FOR EVERY 7 GPM PER ZONE. LOCATE AT LOW POINTS. FLUSH RATE IS 0.8 GPM. FLUSH PRESSURE IS 2 PSI. REFER TO TORO PUBLICATION #ALT111 FOR SPECIFICATIONS.
2. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
3. DO NOT SCALE DRAWING.
4. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
5. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.



DRIP IN® 17MM DRIPLINE

FLUSH VALVE ON POLY-ELBOW