




TORO-IRRIGATION DIVISION
5825 JASMINE STREET
RIVERSIDE, CA 92504
TOLL FREE: 1-877-345-8676
FAX: (951) 359-1870
crc@toro.com
www.toro.com



LEGEND:

- ① TORO AUTOMATIC FLUSH VALVE (T-FCH-H-FIPT) PLUMBED TO FLUSH MANIFOLD AT LOW POINT.
- ② PVC FLUSH MANIFOLD.
- ③ TORO DL2000 OPERATION INDICATOR (T-DL-MP9), OPTIONAL.
- ④ TORO DL2000 MANIFOLD-TO-ELBOW CONNECTION (TYP).
- ⑤ TORO DL2000 DRIPLINE LATERAL (RGP-XXX-XX).
- ⑥ AREA PERIMETER.
- ⑦ PERIMETER LATERALS 2" TO 4" FROM EDGE.
- ⑧ PVC LATERAL LINE FROM DRIP ZONE KIT.
- ⑨ TORO TRI-LOC TEE (TL-T).
- ⑩ PVC SUPPLY MANIFOLD.
- ⑪ TORO AIR/VACUUM RELIEF VALVE (T-YD-500-34) PLUMBED TO SUPPLY MANIFOLD AT HIGH POINT.

NOTES:

- 1. THE TOTAL LENGTH OF ALL INTERCONNECTED DRIP LINE SHALL NOT EXCEED THE MAXIMUM RUN LENGTH. SEE TORO SUBSURFACE IRRIGATION DESIGN GUIDE (FORM #ALT111).
- 2. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
- 3. DO NOT SCALE DRAWING.
- 4. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
- 5. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
- 6. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 065-188I.

