


SECTION/ELEVATION
NOT TO SCALE

LEGEND:

- ① 1" ABOVE FINISH GRADE.
- ② FINISH GRADE.
- ③ 6" ROUND PLASTIC VALVE BOX. HEAT BRAND "AR" ON LID IN 1" HIGH CHARACTERS.
- ④ TORO AIR/VACUUM RELIEF VALVE (T-YD-500-34).
- ⑤ TORO TRI-LOC X 1/2" FPT TEE (TL-T-F50).
- ⑥ TORO DL2000 TUBING (RGP-XX-XXX) OR TORO BLUE STRIPE POLY TUBING (T-EHD1645-XXX) AIR-RELIEF LATERAL.
- ⑦ PEA GRAVEL SUMP (6" DEEP).
- ⑧ BRICK SUPPORTS (2 COMMON BRICKS REQUIRED).
- ⑨ NATIVE SOIL PER SPECIFICATIONS.

NOTES:

1. USE ONE AIR/RELIEF VALVE FOR EVERY 7 GPM PER ZONE. LOCATE AT HIGH POINTS. REFER TO TORO PUBLICATION #ALT111 FOR SPECIFICATIONS.
2. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
3. DO NOT SCALE DRAWING.
4. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
5. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
6. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 065-188p.



DL2000®

AIR/VACUUM RELIEF VALVE ON TUBING