


TORO-IRRIGATION DIVISION 5825 JASMINE STREET RIVERSIDE, CA 92504 TOLL FREE: 1-877-345-8676

FAX: (951) 359-1870

crc@toro.com www.toro.com



LEGEND:

- (1) IRRIGATION CONTROLLER
- ② SENSOR RECEIVER SECURED TO WALL WITH APPROPRIATE FASTENERS AND WIRED TO THE IRRIGATION CONTROLLER'S 24V TERMINAL AND SENSOR PORT (OR COMMON WIRE).
- (3) SENSOR PROBE INSTALLED IN A REPRESENTATIVE AREA OF THE GROUNDS.
- (4) DISTANCE BETWEEN SENSOR PROBE AND RECEIVER NOT TO EXCEED 500 FEET LINE OF SIGHT.
- (5) FINISHED GRADE.

NOTES:

- 1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
- 2. DO NOT SCALE DRAWING.
- 3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
- 4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
- CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 065-467A.



PRECISION SOIL SENSOR APPLICATION VIEW

WIRELESS SOIL MOISTURE SENSOR

065-467A REVISION DATE 08/14/2014